

# FEROCIOUS

## SERIES 2000

- ✓ STANDARD, LONG AND EXTRA LONG LENGTHS
- ✓ 2 FLUTE
- ✓ GROUND WITH MICRO POLISHED CYLINDRICAL LAND FOR IMPROVED SURFACE FINISHES
- ✓ HIGH PERFORMANCE IN ROUGHING, SLOTTING, PERIPHERAL, AND FINISH MILLING
- ✓ HIGH HELIX FOR VERTICAL SHEAR ACTION AND CHIP EVACUATION
- ✓ MANUFACTURED FROM PREMIUM SUB MICRO GRAIN CARBIDE FOR HIGH TRANSVERSE RUPTURE STRENGTH
- ✓ INDUSTRY'S HIGHEST ATTAINABLE SPEEDS AND FEEDS WHEN MILLING ALUMINUM, NON-FERROUS MATERIALS, AND PLASTICS



EDP#	DIA	SHANK	LOC	OAL
2000	9/64	3/16	5/8	2
2001	1/8	1/8	1/2	1-1/2
2002	5/32	5/32	3/4	2
2003	3/16	3/16	5/8	2
2006	1/4	1/4	3/4	2-1/2
2009	1/4	1/4	1-1/4	3
2012	5/16	5/16	1	2-1/2
2015	5/16	5/16	1-3/8	3
2017	11/32	3/8	7/8	2-1/2
2018	3/8	3/8	1	2-1/2
2021	3/8	3/8	1-1/2	3
2024	3/8	3/8	2-1/2	4
2027	7/16	7/16	1	3
2030	1/2	1/2	1	3
2033	1/2	1/2	1-1/4	3
2036	1/2	1/2	1-1/2	3-1/2
2039	1/2	1/2	2	4
2042	1/2	1/2	3	5
2045	9/16	9/16	1-1/4	3-1/2
2048	5/8	5/8	1-1/4	3-1/2
2051	5/8	5/8	1-3/4	4
2054	5/8	5/8	2-1/2	5
2057	3/4	3/4	1-1/2	4
2060	3/4	3/4	2-1/2	5
2063	3/4	3/4	3-1/2	6
2066	1	1	1-1/2	4
2067	1	1	2-1/2	5
2069	1	1	4	7

**NEW**

**ADD THE FOLLOWING AFTER EDP#**

- UC = UNCOATED
- S = ZRN COATED

**TOLERANCES**  
**CUTTING DIAMETER**  
 + .000/ - .0005  
**SHANK DIAMETER**  
 + .000 / - .0005