

# THE STORM

## SERIES 3000

- ✓ STANDARD LENGTH
- ✓ 3 FLUTE
- ✓ GROUND WITH ECCENTRIC RELIEF TO PROVIDE EXTRA STRENGTH AND STABILITY TO THE CUTTING EDGE
- ✓ A HIGH PERFORMANCE END MILL USED IN THE MILLING OF STAINLESS STEELS, TITANIUM, INCONEL, AND NICKEL BASED ALLOYS



THE STORM - 60 DEGREE HI-HELIX STANDARD LENGTH END MILLS

EDP#	DIA	SHANK	LOC	OAL
3001	1/8	1/8	1/2	1-1/2
3003	3/16	1/4	5/8	2-1/2
3006	1/4	1/4	3/4	2-1/2
3009	5/16	5/16	13/16	2-1/2
3012	3/8	3/8	1	2-1/2
3015	7/16	7/16	1	3
3018	1/2	1/2	1	3
3024	5/8	5/8	1-1/4	3-1/2
3030	3/4	3/4	1-1/2	4
3033	1	1	1-1/2	4

### ADD THE FOLLOWING AFTER EDP#

-UC = UNCOATED  
 -ALTiN = ALUMINUM TITANIUM NITRIDE

TOLERANCES  
 CUTTING DIAMETER  
 + .000/ - .002  
 SHANK DIAMETER  
 + .000 / - .0005