

SERIES 590

SPOTTING DRILL 90 DEGREE POINT



EDP#	DIA	SHANK	LOC	OAL
590-1250	1/8	1/8	9/16	1-1/2
590-1875	3/16	3/16	3/4	2
590-2500	1/4	1/4	1	2-1/2
590-3125	5/16	5/16	1	2-1/2
590-3750	3/8	3/8	1	2-1/2
590-5000	1/2	1/2	1-1/4	3
590-6250	5/8	1/2	1-1/4	3
590-7500	3/4	1/2	1-3/4	3-1/2

TOLERANCES
SHANK DIAMETER
+ .000 / - .0005

USED TO PROVIDE TRUE AND ACCURATE
STARTING LOCATIONS

SERIES 520

SPOTTING DRILL 120 DEGREE POINT



EDP#	DIA	SHANK	LOC	OAL
520-1250	1/8	1/8	9/16	1-1/2
520-1875	3/16	3/16	3/4	2
520-2500	1/4	1/4	1	2-1/2
520-3125	5/16	5/16	1	2-1/2
520-3750	3/8	3/8	1	2-1/2
520-5000	1/2	1/2	1-1/4	3
520-6250	5/8	1/2	1-1/4	3
520-7500	3/4	1/2	1-3/4	3-1/2

TOLERANCES
SHANK DIAMETER
+ .000 / - .0005

USED IN MATERIALS SUCH AS STEELS,
ALUMINUM, AND ABRASIVE MATERIALS