


SERIES M130

3 FLUTE STANDARD LENGTH SQUARE END




EDP#	DIA	SHANK	LOC	OAL
130-030	3	3	12	38
130-040	4	4	14	50
130-050	5	5	16	50
130-060	6	6	20	63
130-080	8	8	20	63
130-100	10	10	25	63
130-120	12	12	25	75

TOLERANCES (MM)
 CUTTING DIAMETER
 + .000 / - .050
 SHANK DIAMETER
 + .000 / - .0125

IDEAL FOR SLOTTING AND PERIPHERAL
 MILLING WHEN INCREASED SPEEDS AND
 FEEDS ARE NEEDED

SERIES M230

3 FLUTE STUB LENGTH SQUARE END



EDP#	DIA	SHANK	LOC	OAL
230-030	3	3	6	38
230-040	4	4	8	50
230-050	5	5	10	50
230-060	6	6	12	50
230-080	8	8	12	50
230-100	10	10	16	50
230-120	12	12	19	63

TOLERANCES (MM)
 CUTTING DIAMETER
 + .000 / - .050
 SHANK DIAMETER
 + .000 / - .0125

ADD THE FOLLOWING AFTER EDP#
 -UC = UNCOATED
 -ALTiN = ALTiN COATED
EXAMPLE:
 130-211-ALTiN (ALTiN COATED)
 130-211-UC (UNCOATED)