






















- 3 Flute, 60° Hi-Helix
- Free Cutting Geometry
- Ground with HD Eccentric Relief for Extra Strength and Stability to the Gutting Edge
- High Performance End Mill Used in the Milling of Stainless Steels, Titanium, Inconel & Nickel Based Alloys
- Reduced Neck & Weldon Flats Available Upon Request






Special Sizes, Lengths and Radii Available **Upon Quote Request** 

**ALTIN Coated tools:** Add "ALTIN" After Each Part #


> Other Coatings Available **Upon Request**





## Brand X

- Edge is Relatively Weak Does not Support Radial Forces
- Has Minimal Contact Area for Wear





- CGS -Edge has Full Support Higher Feed Rates Progressive Wear is Countered by the Increased Flute Thickness



Storm Standard Square End 3FL - Stub. Standard, & Long Length Sizes	Cutting Diameter Tolerances +.000"/002"	Shank Diameter Tolerances +.000"/0005"
3FL - Stub, Stanuaru, & Long Length Sizes		

3FL - Stub, Standard, & Long Length Sizes						
EDP#	DIA	SHANK	LOC	OAL	FLUTE	
3001	1/8"	1/8"	1/2"	1-1/2"	3 FL	
3002	5/32"	3/16"	1/2"	2"	3 FL	
3003	3/16"	3/16"	5/8"	2"	3 FL	
3103	3/16"	3/16"	1"	2-1/2"	3 FL	
3004	7/32"	1/4"	3/4"	2-1/2"	3 FL	
3006	1/4"	1/4"	3/4"	2-1/2"	3 FL	
3106	1/4"	1/4"	1"	2-1/2"	3 FL	
3107	1/4"	1/4"	1-1/4"	2-1/2"	3 FL	
3009	5/16"	5/16''	13/16"	2-1/2"	3 FL	
3012	3/8"	3/8"	1"	2-1/2"	3 FL	
3108	3/8"	3/8"	1-1/8"	2-1/2"	3 FL	
3109	3/8"	3/8"	1-1/2"	3"	3 FL	
3015	7/16"	7/16"	1"	3"	3 FL	
3018	1/2"	1/2"	1"	3"	3 FL	
3112	1/2"	1/2"	1-1/4''	3"	3 FL	
3113	1/2"	1/2"	1-1/2"	3-1/2"	3 FL	
3115	1/2"	1/2"	2"	4"	3 FL	
3021	9/16"	9/16''	1-1/4"	3-1/2"	3 FL	
3024	5/8"	5/8"	1-1/4''	3-1/2"	3 FL	
3116	5/8"	5/8"	1-3/4"	4''	3 FL	
3030	3/4"	3/4"	1-1/2"	4''	3 FL	
3121	3/4"	3/4"	2"	4''	3 FL	
3124	3/4"	3/4"	2-1/2"	5"	3 FL	
3127	3/4"	3/4"	3-1/2"	6"	3 FL	
3033	1"	1"	1-1/2"	4''	3 FL	
3136	1"	1"	4''	7''	3 FL	
3137	1"	1"	6"	9"	3 FL	